

Planar Cores (9580200602)



Part Number: 9580200602

80-EQ Core-EQ20/6.4/14

Planar EQ and EQI cores, with their low profile, are suitable for board level installation allowing assembly without the need for plastic coilformers and can also allow windings integrated into multilevel PCBs. Planar EQ cores with their low mass and low profile are suitable for Surface Mount installations in low power filter and transformer applications.

– Planar EQ and EQI cores can be supplied with the center post gapped to a mechanical dimension, or an $A_{\scriptscriptstyle L}$ value.

Catalog Drawing 3D Model

Weight: 5.1 (g)

mm	mm tol	nominal inch	inch misc.
20.0	± 0.35	0.787	_
6.35	± 0.10	0.248	_
14.00	± 0.30	0.551	_
4.10	± 0.15	0.161	_
18.0	± 0.35	0.709	_
8.8	± 0.15	0.346	_
12.50	±Min	0.492	_
	20.0 6.35 14.00 4.10 18.0 8.8	20.0 ± 0.35 6.35 ± 0.10 14.00 ± 0.30 4.10 ± 0.15 18.0 ± 0.35 8.8 ± 0.15	$20.0 \pm 0.35 0.787$ $6.35 \pm 0.10 0.248$ $14.00 \pm 0.30 0.551$ $4.10 \pm 0.15 0.161$ $18.0 \pm 0.35 0.709$ $8.8 \pm 0.15 0.346$




Chart Legend

 Σ l/A : Core Constant, $l_{\rm e}$: Effective Path Length, $A_{\rm e}$: Effective Cross-Sectional Area, $V_{\rm e}$:

Effective Core Volume A_L : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties			
$A_L(nH)$	1210		
Ae(cm ²)	0.600		
$\Sigma l/A(cm^{-1})$	5.53		
l _e (cm)	3.33		

Electrical Properties		
$V_e(cm^3)$	2.000	
$A_{\min}(\text{cm}^2)$	0.550	

 $A_{\scriptscriptstyle L}$ value is measured at 1 kHz, B < 10 gauss.

 $\underline{9580200602}$ is mated with $\underline{9380054002}.$

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288

888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com