

Part Number: 9595282802

95 EER CORE SET

EER cores, similar to ETD cores, have been designed to make optimum use of a given volume of ferrite material for maximum throughput power. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses.

EER cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

[Catalog Drawing](#)
[3D Model](#)

Weight indicated is per pair or set.

Weight: 28 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	28.5	± 0.60	1.122	—
B	14	± 0.20	0.551	—
C	11.4	± 0.30	0.449	—
D	9.6	± 0.20	0.378	—
E	21.2	min	0.835	min
F	9.9	± 0.30	0.39	—




Chart Legend

$\Sigma l/A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross-Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	3500 $\pm 25\%$
A_e (cm ²)	0.859
$\Sigma l/A$ (cm ⁻¹)	7.3

Electrical Properties	
$l_e(\text{cm})$	6.29
$V_e(\text{cm}^3)$	5.398
$A_{\min}(\text{cm}^2)$	0.77

A_L value is measured at 1 kHz, $B < 10$ gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com