

Part Number: 9595394002

95 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched-mode power supplies and permit off-line designs where IEC and VDE isolation requirements must be met.

□ETD cores can be supplied with the center post gapped to a mechanical dimension or an  $A_L$  value.


[Catalog Drawing](#)

[3D Model](#)

Weight indicated is per pair or set.

Weight: 60 (g)

| Dim | mm   | mm tol     | nominal inch | inch misc. |
|-----|------|------------|--------------|------------|
| A   | 39.1 | $\pm 0.70$ | 1.539        | —          |
| B   | 19.8 | $\pm 0.20$ | 0.78         | —          |
| C   | 12.7 | $\pm 0.35$ | 0.5          | —          |
| D   | 14.6 | $\pm 0.20$ | 0.575        | —          |
| E   | 29.3 | min        | 1.154        | min        |
| F   | 12.7 | $\pm 0.35$ | 0.5          | —          |



## Chart Legend

$\Sigma l/A$  : Core Constant,  $l_e$  : Effective Path Length,  $A_e$  : Effective Cross-Sectional Area,  $V_e$  : Effective Core Volume

$A_L$  : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

| Electrical Properties |                 |
|-----------------------|-----------------|
| $A_L$ (nH)            | 3600 $\pm 25\%$ |

| Electrical Properties        |       |
|------------------------------|-------|
| $A_e(\text{cm}^2)$           | 1.28  |
| $\Sigma l/A(\text{cm}^{-1})$ | 7.2   |
| $l_e(\text{cm})$             | 9.24  |
| $V_e(\text{cm}^3)$           | 11.85 |
| $A_{\min}(\text{cm}^2)$      | 1.267 |

$A_L$  value is measured at 1 kHz,  $B < 10$  gauss

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288  
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • [ferrites@fair-rite.com](mailto:ferrites@fair-rite.com) • [www.fair-rite.com](http://www.fair-rite.com)