

Part Number: 9598343502

98 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched-mode power supplies and permit off-line designs where IEC and VDE isolation requirements must be met.

□ETD cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 40 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	34.2	± 0.65	1.346	-
B	17.3	± 0.20	0.681	-
C	10.8	± 0.30	0.425	-
D	12.1	± 0.20	0.476	-
E	25.6	min	1.008	min
F	10.8	± 0.30	0.425	-




Chart Legend

$\Sigma l/A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross-Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	2600 ±25%
A_e (cm ²)	0.972
$\Sigma l/A$ (cm ⁻¹)	8.2
l_e (cm)	7.9

Electrical Properties	
$V_e(\text{cm}^3)$	7.68
$A_{\text{min}}(\text{cm}^2)$	0.916

A_L value is measured at 1 kHz, $B < 10$ gauss

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com