

## Cortificate of Cores (8995121221)



Part Number: 8995121221

95 EFD CORE SET

EFD (Economical Flat Design) cores have been designed to maximize volume in a low profile geometry. EFD cores allow maximum throughput power density with reasonably low mass for board level installation.

EFD cores can be supplied with the center post gapped to a mechanical dimension or an A<sub>I</sub> value.

## Catalog Drawing 3D Model

Weight indicated is per pair or set.

Weight: 1.8 (g)

Dim	mm	mm tol	nominal inch	inch misc.	
A	12.5	± 0.35	0.492	_	←B ←C→
В	6.2	± 0.15	0.244	_	
С	3.5	± 0.20	0.138	_	F E
D	4.55	± 0.15	0.179	_	
Е	9	± 0.35	0.354	_	
F	5.4	± 0.20	0.213	_	
K	2	± 0.10	0.079	_	30000 Paris 100

## **Chart Legend**

 $\Sigma l/A \ : \ Core \ Constant, \quad l_{_e}: \ Effective \ Path \ Length, \quad A_{_e}: \ Effective \ Cross-Sectional \ Area, \quad V_{_e}:$ 

Effective Core Volume  $A_L$ : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

<b>Electrical Properties</b>		
$A_L(nH)$	850 ±25%	
Ae(cm <sup>2</sup> )	0.11	
$\Sigma l/A(cm^{-1})$	25.9	
$l_e(cm)$	2.84	

<b>Electrical Properties</b>				
$V_{\rm e}({\rm cm}^3)$	0.311			
$A_{\min}(\text{cm}^2)$	0.108			

 $A_{\scriptscriptstyle L}$  value is measured at 1 kHz, B < 10 gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288 888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com