

Part Number: 5695110821

95 POT CORE SET

Pot cores have found application in all types of inductive devices. The core configuration provides a high degree of self-shielding. It also facilitates gapping to enhance utility for a variety of magnetic designs.

□Pot cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 1.9.000 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	11.1	±0.20	0.437	—
B	3.3	±0.10	0.13	—
C	6.8	±0.25	0.268	—
D	2.3	±0.15	0.091	—
E	9.2	±0.20	0.362	—
F	4.6	±0.10	0.181	—
G	2.2	±0.30	0.087	—





Chart Legend

$\Sigma l/A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross-Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	1900 ±25%
A_e (cm ²)	0.173
$\Sigma l/A$ (cm ⁻¹)	9.5

Electrical Properties	
l_e (cm)	1.65
V_e (cm ³)	0.284
A_{min} (cm ²)	0.145

A_L value is measured at 1 kHz, $B < 10$ gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com