

# Flat Cable EMI Suppression Cores (2643166551)



Part Number: 2643166551

43 FULL FLAT CABLE CORE

#### **Explanation of Part Numbers:**

- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade

Flat cable suppression core can accommodate multi-conductors flat cables, in widths from 12.7 mm (0.500) up to 77 mm (3.0). These flat cable cores are available in two ferrite material grades to reduce conducted EMI from 1 MHz to hundreds of MHz.

Our Expanded Cable & Suppressor Kit (part number 0199000005) contains a selection of these flat cable cores and clips.

Flat Cable Cores are available in selected sizes in the Flex Circuit & Ribbon Cable Core Kit (part number 0199000038).


Assembly clips are available for most of the split flat cable cores. See section Flat Cable Cores Assembly clips.

## Catalog Drawing 3D Model

<u>Weight:</u> 71 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	45.1	±0.75	1.776	_
В	34.4	±0.70	1.354	_
С	28.6	±0.70	1.126	_
D	12.45	±0.40	0.49	_
E	1.5	±0.30	0.059	_

Cable Information					
Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores		
0	33.70 x 1.20	_	-		



### **Chart Legend**

- + Test frequency
- •For assembly clips see Flat Cable Cores Assembly Clips


Typical Impedance (Ω)		
10 MHz	80	
25 MHz <sup>+</sup>	128	
100 MHz <sup>+</sup>	263	
250 MHz	475	

Flat cable suppression cores, split or single cores, are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

#### **Catalog Drawing**

Centered, single turn impedance tests for the 31 and 43 material parts are performed on the E4990A Impedance Analyzer. All tests are made with the shortest practical wire length.

Typical Impendance ( $\Omega$ )				
10 MHz	67			
25 MHz <sup>+</sup>	115			
100 MHz <sup>+</sup>	300			
250 MHz	415			



#### **CSV** Download

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288 888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com