

## Round Cable Snap-It<sup>™</sup> (0461176451)



Part Number: 0461176451

61 ROUND CABLE CORE ASSEMBLY

## **Explanation of Part Numbers:**


- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade

Round cable snap-it<sup>m</sup> can easily accommodate round cables or bundled wires with diameters from 2.5 mm (0.100) to 25.4 mm (1.000). These assemblies are available in four ferrite material classes to suppress differential or common-mode conducted EMI from 1 MHz into the GHz region. The polypropylene cases are meeting the RoHS restrictions of hazardous substances and have a flammability rating of UL 94 V-0.

Many of the snap-it<sup>™</sup> parts have round core equivalents. See Round Cable EMI Suppression Cores.

Round Cable Snap-It<sup>m</sup> Kits are available for each of the four suppression materials. 31 Snap-It<sup>m</sup> Kit (0199000030), 43 Snap-It<sup>m</sup> Kit (0199000031), 46 Core and Snap-It<sup>m</sup> Kit (0199000032) and 61 Snap-It<sup>m</sup> Kit (0199000033).

Catalog Drawing
3D Model




The B dimension is the core inside diameter.

Weight: 161 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	38.5	+/- 1.5	1.516	1
В	18.00	_	0.709 min	
С	47.5	+/- 2.0	1.87	_
D	19.15	+/- 1.5	0.755	

Cable Information						
Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores			
18 0.709	_	_	-			



## **Chart Legend**

- + Test frequency
- For solid cable cores, see Round Cable EMI Suppression Cores


Typical Impedance $(\Omega)$				
100 MHz	341			
250 MHz <sup>+</sup>	534			
500 MHz <sup>+</sup>	485			
1000 MHz	235			

Round cable snap-it  $^{\text{\tiny TM}}$  assemblies are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

## **Catalog Drawing**

Single turn impedance tests for 31, 43 and 46 material cores are performed on the E4991A/HP4291B Impedance Analyzer. The 61 material parts are tested on the E4991A / HP4291B Impedance Analyzer and 75 material parts are tested on the E4990A Impedance Analyzer. Cores are tested with the shortest practical wire length.

Typical Impendance ( $\Omega$ )100 MHz360250 MHz<sup>+</sup>480500 MHz<sup>+</sup>3501000 MHz110



Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com