

Part Number: 9579180302


79 ER CORE

Planar EE and EI cores, with their low profile are suitable for board level installation allowing assembly without the need for plastic coil formers and can also allow windings integrated into multi-level PCBs. Planar ER cores with their low mass and low profile are suitable for Surface Mount installations in low power filter and transformer applications.

-Planar EE, ER and EI cores can be supplied with the center post gapped to a mechanical dimension, or an  $A_L$  value.


Weight: 1.85 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	18.00	0.35	0.709	—
B	3.15	± 0.10	0.124	—
C	9.7	± 0.20	0.382	—
D	1.60	± 0.10	0.063	—
E	15.60	± 0.30	0.614	—
F	06.20	0.15	0.244	—



### Chart Legend

$\Sigma l/A$  : Core Constant,  $l_e$  : Effective Path Length,  $A_e$  : Effective Cross-Sectional Area,  $V_e$  : Effective Core Volume

$A_L$  : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
$A_L$ (nH)	21 Min
$A_e$ (cm <sup>2</sup> )	30.2
$\Sigma l/A$ (cm <sup>-1</sup> )	0.730
$l_e$ (cm)	22.1
$V_e$ (cm <sup>3</sup> )	667
$A_{min}$ (cm <sup>2</sup> )	30.1

$A_L$  value is measured at 1 kHz,  $B < 10$  gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288  
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • [ferrites@fair-rite.com](mailto:ferrites@fair-rite.com) • [www.fair-rite.com](http://www.fair-rite.com)